



SEA BOX[®]

Quadcon Refrigerated ISO Cargo Container

SB530-0
 Quadcon Refrigerated ISO Cargo Container



Internal lighting



Stainless Steel lining



Fully adjustable shelving "A" tracks



Temperature Control Display

PRODUCT FEATURES

STANDARD FEATURES

- Smooth Steel sides, roof + single swing doors
- Stainless Steel lining
- Heavy duty tread plate aluminum floor
- Four way fork lift pockets
- 208/230 Volts AC Electric Refrigeration Machinery, 3 phase; 60 cycle
- Temperature range from -20° F to 80° F
- Temperature Control display adjacent to entry door
- Fully adjustable shelving "A" tracks, fully recessed into the walls

OPTIONAL FEATURES

- Connecting couplers, (3) per Quadcon
- Connecting coupler storage bracket (1) each
- Manifest box (2) each
- SS shelving (8) pieces, open wire design
- SS decking and shoring beams (16) each
- Spare parts box

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	4' 9 3/8"	4' 5 3/4"	8' 0"	7' 1/8"	8' 0"	7' 5 3/16"	6'	2' 4 1/4"
Metric	1,457	1,365	2,438	2,137	2,438	2,265	1,829	718

	TARE WEIGHT w/ MACHINE	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY	THERMAL LEAKAGE = U MAX @ 10°C MEAN TEMP
Lbs	2,600	9,300	11,900	195 Cu. Ft.	95 BTU/h°F
Kgs	1,179	4,219	5,398	5.52 Cu. M.	52.88 Kcal/h°C

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

000000-R00

ISO 9001:2008



CERTIFIED QUALITY
MANAGEMENT SYSTEM

CONTRACT # GS-02F-0024P
GSA Advantage![™]