



# SEA BOX®

## 20ft X 8ft 6in Refrigerated ISO Cargo Container



20' Stainless Steel Refrigerated Container



Road Side Cargo Door Front Compartment w/ 2 Shelf Sets



Rear Compartment w / 3 Shelves

### STANDARD PRODUCT FEATURES

- One (1) set of laden fork lift pockets
- One (1) Double full opening swing cargo doors on one end with sealable screened ventilation port, SS Hinges + SS Locking bars
- One (1) Single cargo door on one side
- Emergency Escape Door hardware on both Rear and Side doors
- Heavy duty aluminum floor, reinforced for pallet use
- Refrigeration unit: CARRIER Model # 69-NT40 220/230, 380/460 VAC, 3 phase, 50-60 Hz 220/230 plug & 380/460 plug
- Temperature range from -25C to 25C
- One (1) Moveable Interior wall partition (creates 2 compartments)
- Two (2) Internal lights with (2) switches (1 per compartment)
- Two (2) "Locked In" alarm buttons (1 per compartment)
- Five (5) sets Shelves, food grade, flat packed, w/ 5 web straps
- Brackets for Clip-On Generator are provided
- Warranty, 3 year workmanship
- Certified: ATP, NZ, AU, EEC, USDA Health Code & Food Hygiene, NSF Certified
- ISO Certified, Customs Approved, UIC, TIR
- Operations Manual and Parts List Manual

### OPTIONAL PRODUCT FEATURES

- Two (2) each, single interior outlets, 115 VAC, 1 phase, 60 Hz, 15 amp, NEMA L15 (1 per compartment)
- Clip-On Gen Set: 15 KW, 400/460 VAC, 3 Phase, 50-60 Hz
- Carrier Reefer Unit may be equipped with 30 amp CEE heavy duty outlet with mechanical interlock switch to run only 1 reefer at a time
- Carrier Reefer Unit may be equipped with 60 amp CEE heavy duty outlet, to run 2 reefers at a time. Also upgrade SO cable and 460 VAC plug to 60 amp rated
- De-Humidity controls on the Carrier Reefer Unit
- Shelving, an upgrade from shelving flat packed in cardboard box to be fully assembled and installed, strapped to the interior walls of the container



Moveable Partition makes 2 Compartments



2 Light Switches on for each Compartment

### ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD FOR NINE (9) HIGH STACKING

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
<b>Ft in</b>	19' 10 1/2"	17' 5 1/2"	8' 6"	7' 4 1/2"	8' 0"	7' 4"	7' 4 1/2"	7' 4"
<b>Metric</b>	6,058	5,321	2,591	2,248	2,438	2,235	2,248	2,235
	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		CUBIC CAPACITY	
<b>Lbs</b>	6,880		60,320		67,200		944 Cu. Ft.	
<b>Kgs</b>	3,120		27,360		30,480		26.7 Cu. M.	

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

**SB541-6-UN**  
 20ft X 8ft 6in Refrigerated ISO Cargo Container



NSF Certified Production effective Jan 26, 2009

052411-R00

ISO 9001:2008



CERTIFIED QUALITY MANAGEMENT SYSTEM