

CORPORATE OFFICE 802 Industrial Hwy. East Riverton, NJ 08077-1910 Tel: (856) 303-1101 Fax: (856) 303-1501 www.seabox.com e-mail: sales@seabox.com



20' Collapsible Shelter

20' ISO Container	Length		Height		Width		Tare Weight
	Exterior	Interior	Exterior	Interior	Exterior	Interior	
Feet/Inches	19' 10 1/2''	19' 4 11/64''	9' 0''	8' 0''	8' 0''	7' 8 17/32''	4,299 lbs.
Metric	6,058	5,897	2,743	2,438	2,438	2,350	1,950 kg

— STANDARD FEATURES —

- Collapsible Kit, 2' high can be stacked 4 high
- Constructed Unit, 9' 0" high can be stacked 3-high
- (2) sets of forklift pockets, laden and unladen
- Insulated wall panels: 9'6" H x 3.75' W x 2.75" (thick)
 5 (each) per long side, fully interchangeable,
- 2 (each) per short side 1 external door: 7' H x 3' W x 2" D furnished with
- handle lock, pre-painted aluminum frame
- ► 2 (each) double layer windows (32" x 43")
- "Sliding" mechanism (one side fixed and one sliding) Electrical components
- Distribution box, 110V single phase
 - (2) overhead lights
 - flush mounted (2) sockets and (1) switches
- Units can be connected to create a larger structure
- ► Thermal Conductivity Coefficient: 0.039 W/mK
- ► Thermal Resistance (R21 Value): 1.28 m²K/W
- Combination Heating/Cooling unit (110V)

- OPTIONAL FEATURES -

- Plastic PVC rolling shutters provided
- Anti Vandal Bars for windows
- Anti Vandal Gate for door
- Resin floor covering
- Connection Kits (create larger structures)



20' Collapsible Container Interior



Create larger structures with connected units



Pre-Assembled Kit (2' high) Can be stacked 4-high

PART # SB3893.9 MH101