

STANDARD FEATURES

- · Can be connected to create larger complexes in multi-story configurations up to 3 modules high
- · Heavy duty 4" cold-formed steel frame
- · Heavy gauge .5mm steel sheathing
- Corrugated steel roof rated for 60 LB/SF snow loads
- 4" mineral wool insulation
- · IBC 2018 Compliant
- Type II B Noncombustible
- · Rated for 150 mph winds
- Conforms to ASCE/SEI 7-16
- Integrated data ports
- · Rated to Seismic Design Category D
- (1) set of standard forklift pockets
- (2) Tilt & turn windows, 48" x 32"
- (1) External door, 78.50" x 33.25" opening
- · Can be transported on flatbed trucks for over the road deliveries
- Telephone/Cable Components - (1) RJ45 receptacles
- (1) HVAC door, 16.25" x 26"
- 7 day programable thermostat
- NEC Compliant Electrical System (120/240 volt, single phase; 2-surface mounted 4' long lighting fixtures; 1-quad receptacle; 2-duplex receptacles; 1-single receptacle; 1-motion sensor switch)

OPTIONAL FEATURES

- · Heating and Cooling Unit: 12,000/10,000 BTU (cool/heat)
- · Stairs and Platforms
- Furniture (desk, tables and chairs)
- Security Window Screens
- · Steel Door, Window, Panic Bar, & Door Closer



Pictured: SB3645.9 LBMO-2, standard 2 window, 1 door setup



Pictured: Interior Office Space



Pictured: 2 level custom MOBU complex. shown with 4 window, 1 door setup





Pictured: Security Window Screen (optional)

	LENGTH		HEIGHT		WIDTH		Tore Weight]
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Tare Weight	
Ft in	19' 10 1/2"	19' 0"	9' 6"	8' 0"	8' 0"	7' 1"	8,650 lbs.]
Metric	6,058	5,791	2,896	2,438	2,438	2,159	3,924 kg.]

111621-R00

ISO 9001



ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

Pictured: Steel Door

w/Window (optional)

Fax: 856 . 303 . 1501 © Copyright 2020, Sea Box, Inc.

Email: sales@seabox.com

www.seabox.com

Phone: 856 . 303 . 1101