



20' X 8' 6" Double Doors One End Standard Dry Freight ISO Cargo Container



STANDARD FEATURES

- Corrugated steel sides, roof + swing doors on (1) end
- 2 way laden forklift pockets
- 1 1/8" thick marine plywood floors, forklift tested to 16,000 lbs per 44 square inches
- Wall tie down steel lashing rings, 4,000 lbs. cap. each (20 total) tested at 6,000 lbs.
- Front corner post tie downs (4 total)
- Door corner post tie downs (4 total) = restraint system, shoring slot will support 2" x 6" lumber (2 per side)
- Vents, (2) each



OPTIONAL FEATURES

- Manifest box (2) each
- 2nd set unladen forklift pockets
- 383 Green exterior CARC paint

NSN: 8150-01-463-8553

213,360 Kgs Minimum Force to be Applied in Stacking Test

SB861.6.NQ	LENGTH (+0/-6)		HEIGHT (+0/-5)		WIDTH (+0/-5)		DOOR OPENING (+0/-5)	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft. in.	19' 10 1/2"	19' 4 13/64"	8' 6"	7' 10 3/8"	8' 0"	7' 8 19/32"	7' 6 1/32"	7' 8 1/8"
Metric	6,058	5,898	2,591	2,397	2,438	2,352	2,287	2,340
	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		CUBIC CAPACITY	
Lbs.	4,650		62,550		67,200		1,170 Cu. Ft.	
Kgs.	2,110		28,370		30,480		33.2 Cu. M.	

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

